







el montadero
BULTACO
CEMOTO

EL MONTADERO OR ”RID



ING PLEASURE".

Its sporting and brilliant running is in harmony with its rapid and safe rhythm; designed for the victor in whatever activity.

El Montadero gives maximum efficiency because it is not an amateur, but a mature product from a strict process. The triple application (on road, mountain or sand), makes the El Montadero a versatile motorcycle, adaptable to all circumstances and preferences.



specifications

BULTACO

ENGINE	**360 cc.**
Number of cylinders	1
Cycle	2 stroke
Bore and stroke	85 x 64 mm.
Displacement	362.8 cc.
Compression ratio	10 : 1
Brake horsepower	32.6 HP at 6000 rpm
Alloy cylinder head and alloy cylinder with hardened liner	
CARBURETOR	AMAL 932 concentric
IGNITION	Dual-Ignition, Electronic System with Battery
GEARBOX	4 speed
Ratios	I . 0.405 : 1 | III . 0.925 : 1 II . 0.645 : 1 | IV . 1.26 : 1
CLUTCH	Multiple plate in oil bath
TRANSMISSION	
Primary transmission	Helicoidal pinnions and primary drive with shock-absorbers
Secondary transmission	5/8" Chain with tensioner
SUSPENSION	
Front suspension	Telescopic with hydraulic dampening (6 1/2" travel)
Rear suspension	Swinging arm with hydraulic dampening (3 15/16" travel)
WHEELS	
Front wheel	3.00 x 21" Knobby Tyre
Rear wheel	4.00 x 18" Knobby Tyre
BRAKES	Internal expanding: leading and trailing shoe
Front brake diameter & width	Ø 140 x 35 mm. (9.600 mm²)
Rear brake diameter & width	Ø 140 x 40 mm. (11.360 mm²)
GENERAL MEASUREMENTS	
Gas-tank capacity	2 3/4 U. S. gallons (10.5 lts.)
Wheelbase	56" (1420 mm.)
Overall length	83" (2110 mm.)
Handlebars width	35 3/4" (910 mm.)
Saddle height above ground	31" (785 mm.)
Ground clearance	10 1/4" (263 mm.)
Foot-rest height	11.22" (285 mm.)
Empty weight	251 lbs. (114 Kgs.)

Constant improvements will subject specifications to change without notice

COMPAÑIA ESPAÑOLA DE MOTORES, S. A.
San Adrián de Besós - Barcelona - SPAIN

Art.° 70.34 - 001 I